

MANUFACTURER

GRANTMAN INDUSTRIAL CORPORATION
 Address : 4935 Emilio Aguinaldo Highway, Talaba IV,
 Bacoor Cavite 4102
 Contact no.: (046) 929 3116 / 927 3086 / 621 9075

PRODUCT NAME

FORTRESS NON SLIP DIAMOND SEALER

PRODUCT DESCRIPTION

FORTRESS NON SLIP DIAMOND SEALER provides beautiful high gloss acrylic protection with a non slip finish to increase surface traction for concrete and stone floorings. This super-tough film gives a strong grip coating, resists chemicals and is abrasion resistant. For use on porous materials, a clear non-yellowing sealer that resists tough oils, water and acid indoors and outdoors while preventing slips and falls. Our deep bonding formula, resists peeling, cracking, uv degradation and efflorescence.

SURFACE PREPARATION

Surfaces must dry, porous and free of foreign contaminants. Make certain that the bond to any previously applied stain or sealer is secure by applying sealer to a small area and check for possible lifting before proceeding. It is recommended to thoroughly remove all previously applied sealer.

COVERAGE

Coverage requirement vary depending upon the porosity of the surface being sealed.

SHELF LIFE

Store in a safe place, out of direct sunlight, heat, sparks and open flame. Keep containers tightly sealed and upright to prevent leakage when not in use. Do not transfer contents into bottles or other unlabeled containers, In case of spillage, absorb, sweep up, and place in a proper waste disposal container.

ADVANTAGES

- ✓ Increase Surface Traction
- ✓ Abrasion Resistant
- ✓ Reinforced with Polymer Beads to Prevent Falls and Skids
- ✓ Best for Concrete and Stone Floorings
- ✓ Environment Friendly
- ✓ For Indoor and Outdoor

COLOR

Transparent

TESTING

Apply on a small area to see if texture is sufficient. To adjust to a finer texture, dilute with FORTRESS Diamond Seal until the desired texture is achieved.

APPLICATION

- Apply 1-2 light even coats (depending on porosity of surface) with a natural brush.
- Do not allow product to puddle. Allow 1-3 hours before light use.
- Use only in well ventilated area.

CAUTION

Do not inhale vapors or mist. Use only with adequate ventilation. Avoid contact with skin and eyes. Close container after each use. Mixed sealer will harden with prolonged exposure in an open container.

LIMITED WARRANTY

This product is warranted to be of uniform quality within manufacturing tolerances. It is best use for concrete and stone floorings. Please test first on all other surfaces before application. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the effects or as a result of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchased price or replacing material proven defective. The end user shall be responsible in determining product's suitability and assumes all risks and liability.

PACKAGING

