

**MANUFACTURER**

**GRANTMAN INDUSTRIAL CORPORATION**  
 Address : 176 H Tandang Sora Ave. Quezon City,  
 Philippines 1116  
 Contact no.: (02) 929 3116 / 927 3086 / 621 9075  
 Mobile no.: 0922 868 0806 / 0917 893 4908 Fax : 930 4142

**PRODUCT NAME**

**FORTRESS GREEN CLEAN**

**PRODUCT DESCRIPTION**

FORTRESS GREEN CLEAN is a non-corrosive biodegradable gel developed to prepare a concrete substrate by producing a moderate surface texture. Green Clean is the next generation in surface preparation.

**COVERAGE**

1 Liter can cover 6.0 - 8.0 square meters depending on surface porosity, profile and application method.

**SHELF LIFE**

FORTRESS GREEN CLEAN can be usable within one (6) months on a unopened container and three (3) months on an open container. Storage Condition is at 40 - 90 degrees Fahrenheit

**ADVANTAGES**

- ✓ Produce a moderate texture on machine troweled concrete
- ✓ Biodegradable
- ✓ User friendly
- ✓ Non-corrosive
- ✓ Low Odor

**SOLID CONTENTS**

FORTRESS GREEN CLEAN 40.2% ± 1% By Weight

**RECOMMENDED FILM THICKNESS PER APPLICATION**

Liberally apply at approximately 4-5 mils thickness

**NOT RECOMMENDED FOR**

Coating removal including paint, sealer and other film forming products.

**COLOR**

Green

**CAUTION**

Use gloves and eye protection. Avoid contact with eyes and prolonged skin contact. If eye contact occurs, wash with clean water and consult a doctor immediately.

**WARRANTY**

FORTRESS GREEN CLEAN is covered from the date of purchase when used on substrate which conforms to local building codes and when installed, in accordance with the manufacturer's instruction. FORTRESS GREEN CLEAN will replace those which are determined to be defective. This warranty is limited to the original purchaser and may not be transferred to any subsequent owner. This warranty does not cover damage resulting from: settlement of the building or other wall movement, mixing with other chemicals or additives and prolonged exposure to heat and other irregular temperature. This warranty covers only manufacturing defects in FORTRESS GREEN CLEAN. It will not cover labor costs or damages obtained from removal and replacement of defective products.

**APPLICATION INSTRUCTION****Area Preparation**

Be sure to mask or cover all areas that are not intended to be prepared with Fortress Green Cleaner.

**Surface Preparation**

The surface preparation phase of "Staining a Concrete Floor" should be viewed as the most important. Proper floor preparation results in the product longevity, minimizes potential failures and creates the best environment for an aesthetically pleasing work of art. In short, the more detail and time allotted to this phase of the project will dramatically affect the appearance and durability of the finished floor.

1. Remove paint, adhesives and loose particulates from the intended application surface.
2. Wetting the intended treatment area with water is recommended for application in hot weather or direct sun exposure.
3. Allow the gel to remain on the substrate for 20 minutes. Do not allow Green Clean to dry on the substrate. Mist water via hose or pump up spray to keep treated area for drying.
4. Allow surface to dry.
5. Perform a "Tape Test".

**Tape Test**

A tape test will help determine the effectiveness of the cleaning process. After the floor has been thoroughly scrubbed, rinsed and allowed to dry; apply several 1 foot strips of high quality 2" clear packaging tape to various locations on the floor. Aggressively press the tape onto the floor with the heel of your hand. Fold one end of the tape into itself and pull it off of the floor as vigorously as possible. Examine the adhesive layer in a bright light looking for residue that was pulled from the floor. Little to no dust or other foreign particles should be visible. Areas with visible foreign material need to be rinsed again until the surface is free of these contaminants.

**Dilution**

Do not dilute Fortress Green Clean.

**Clean Up**

Immediately cleanup work area and tools with water.

**PACKAGING**