

MANUFACTURER

GRANTMAN INDUSTRIAL CORPORATION
Address : 4935 Emilio Aguinaldo Highway, Talaba IV,
Bacoor Cavite 4102
Contact no.: (046) 929 3116 / 927 3086 / 621 9075

PRODUCT NAME

FORTRESS DIAMOND SEALER MATTE SEALER

PRODUCT DESCRIPTION

FORTRESS DIAMOND SEAL MATTE SEALER provides less shine acrylic protection to natural, manufactured stone walls and floors and decorative stamped concrete. This super-tough film gives a rich "MATTE FINISH" appearance, resists chemicals, abrasion and stains. For use on porous materials. A clear, non-yellowing sealer that resists tough oils, water and acid indoors and outdoors. Deep bonding formula resists peeling, cracking and, UV degradation, and efflorescence.

SURFACE PREPARATION

Surfaces must dry, porous and free of foreign contaminants. Make certain that the bond to any previously applied stain or sealer is secure by applying sealer to a small area and check for possible lifting before proceeding. It is recommended to thoroughly remove all previously applied sealer.

COVERAGE

Coverage requirement vary depending upon the porosity of the surface being sealed.

SHELF LIFE

Store in a safe place, out of direct sunlight, heat, sparks and open flame. Keep containers tightly sealed and upright to prevent leakage when not in use. Do not transfer contents into bottles or other unlabeled containers. In case of spillage, absorb, sweep up, and place in a proper waste disposal container.

ADVANTAGES

- ✔ Increase Surface Traction
- ✔ Abrasion Resistant
- ✔ Best for Concrete and Stone Floorings
- ✔ Environment Friendly
- ✔ For Indoor and Outdoor
- ✔ Improve Hardness
- ✔ Water and Stain Resistance

COLOR

Transparent

APPLICATION

- Apply 1-2 light even coats (depending on porosity of surface) with a natural brush.
- Do not allow product to puddle. Allow 1-3 hours before light use.
- Use only in well ventilated area.

CAUTION

Do not inhale vapors or mist. Use only with adequate ventilation. Avoid contact with skin and eyes. Close container after each use. Mixed sealer will harden with prolonged exposure in an open container.

LIMITED WARRANTY

This product is warranted to be of uniform quality within manufacturing tolerances. It is best use for concrete and stone floorings. Please test first on all other surfaces before application. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the effects or as a result of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchased price or replacing material proven defective. The end user shall be responsible in determining product's suitability and assumes all risks and liability.

PACKAGING

