

MANUFACTURER

GRANTMAN INDUSTRIAL CORPORATION
Address : 4935 Emilio Aguinaldo Highway, Talaba IV,
Bacoor Cavite 4102
Contact no.: (046) 929 3116 / 927 3086 / 621 9075

PRODUCT NAME

FORTRESS® SURE GRIP

PRODUCT DESCRIPTION

FORTRESS® SURE GRIP is an easy to apply anti-slip treatment for porcelain, ceramic and other stone surfaces. Creates nano threads to increase coefficient of friction and prevents slippage even when floor is wet.

ADVANTAGES / CUSTOMER BENEFITS

- Easy to apply
- Minimal to no changes in appearance
- Water based formulation, environmentally friendly, fast drying
- For interior and exterior applications

USES

FORTRESS® SURE GRIP is best used in kitchen, pool areas, hotels and resorts, restaurants and factories, hospitals and health care facilities, bathrooms and toilet areas.

SURFACE THAT CAN BE TREATED

- Porcelain
- Ceramic
- Travertine
- Marble
- Granite
- Terrazo
- Concrete
- Slate

NOTE

Avoid contact of FORTRESS® SURE GRIP solution with all metal and glass surfaces. Remove them temporarily or cover with tape. Use with care for metal drain covers for drainages, bathrooms and toilets.

COVERAGE

Coverage requirement may vary depending upon the porosity of the surface, up to 10.00 square meters per liter.

STORAGE / SHELF LIFE

FORTRESS® SURE GRIP has a shelf life of up to 2 years provided its stored in a tightly closed container and protected from sunlight. Do not allow to freeze.

CAUTION

Use gloves and eye protection. Avoid contact with eyes and prolonged skin contact. If eye contact occurs, wash with clean water and consult a doctor immediately.

LIMITED WARRANTY

FORTRESS SURE® GRIP is covered from the date of purchase when used on substrate which conforms to local building codes and when installed, in accordance with the manufacturer's instruction. FORTRESS® SURE GRIP will replace those which are determined to be defective. This warranty is limited to the original purchaser and may not be transferred to any subsequent owner. This warranty does not cover damage resulting from : discoloration resulting from poor quality of the substrate or natural reaction of porous natural stones. ALWAYS test in small remote area and observe surface to check if there are any changes in the color for 3 days before full application. Do not proceed if you unsatisfied with the results. This warranty covers only manufacturing defects in FORTRESS® SURE GRIP. It will not cover labor costs or damages obtained from removal and replacement of defective products.

APPLICATION

WARNING:

ALWAYS test in small remote area and observe surface to check if there are any changes in the color for 3 days before full application. Do not proceed if you unsatisfied with the results.

1. Clean the floor tile surface thoroughly and for best result apply on dry tile.

2. Apply FORTRESS® SURE GRIP on the surface and check the desired friction level is sufficient by applying downward pressure of a rubber sole shoe. Keep the surface evenly wet with FORTRESS SURE GRIP until you achieve your slip resistance level. Monitor the time it takes.

3. Increase friction level will occur 5 - 10 minutes after initial application. When finish, neutralize the area with clean water mixed with baking soda. 4 Liters of water and one tablespoon of baking soda will be good enough. Be careful not over treat the surface with added time exposure to FORTRESS® SURE GRIP. Check if there are any visible changes in color of the surface. Dark colored surface that have inadequate surface hardness will have a tendency to be one shade lighter after application.

4. If there are any visible changes in color, re-test on another area. If there are no changes in the surface color and the slip resistance level has been achieved, you are ready to treat the remaining floor area. If you are not sure, contact Fortress Technical Group for Assistance.

5. For full application of the remaining floor area, use a tank sprayer and a microfiber pad mop on an area where you can manage to maintain the treatment and neutralization process. Divide the total area into smaller sections for effective application. Do not let FORTRESS® SURE GRIP dry on the surface. After treatment, apply neutralizer to stop the chemical process from becoming too tacky. Repeat the process for all sections until the entire floor is treated. Rinse floor entirely with clean water and air dry to complete the process. Your floors are now Slip Free!

PACKAGING

